



# Finish Care

Care emulsion for initial and maintenance cleaning

## Description:

Water-based emulsion for high-quality care of flooring surfaces.

Especially suitable for the surface treatment of:

- Sealed parquet flooring
- Sealed cork flooring
- Pre-finished parquet
- Linoleum
- PVC
- Natural and artificial stone flooring



## Product Properties / Benefits:

Water-based care emulsion that, by means of a dirt-repellent protective film, improves the seal and appearance of the surface, and at the same time extends the wear life of the flooring.

- Ready to use
- Easy to apply
- Hard wearing
- Rapid drying
- No polishing required
- Formaldehyde-free
- Solvent-free

## Technical Data:

Packaging:	plastic canister/bottle
Packsizes:	0.75 litre
Lustre value:	semi-matt, matt
Shelf life:	approx. 12 months
Colour:	white
Initial clean/consumption:	approx. 7 – 10 ml/m <sup>2</sup>
Maintenance/consumption:	approx. 100 – 250 ml/10 litre

# Finish-Care

---

## Surface Preparation:

Using a mop, soft brush or vacuum cleaner, ensure that the flooring is free from dirt, dust, grease, oil or wax.

## Application:

1. Before use, shake the container well.
2. Initial clean:  
Apply a thin, even coat of Pallmann Finish-Care using approx. 10 ml undiluted and applied with a sponge, mop or polishing machine. No buffing is required. After approx. 60 minutes, the surface can be used.
3. Maintenance:  
Dilute approx. 100 – 250 ml Pallmann Finish-Care with 10 litres of water and apply thinly with a sponge, cloth or mop. After 60 minutes, the surface can be used. This maintenance should be carried out as required.

## Important Notes:

- Shelf life minimum 12 months in original packaging when stored in constant conditions. Protect from frost. Tightly reseal opened containers.
- Optimum conditions are 18 to 25 °C and relative humidity < 65 %. Low temperatures and high humidity lengthen, high temperatures and low humidity shorten the drying time.
- Leave freshly sealed surfaces until fully hardened (depending on the seal system used) before treating with Pallmann Finish-Care.
- Regular maintenance with Pallmann Finish-Care improves the appearance and increases the wear life of the sealed surface.
- Leave freshly sealed surfaces at least one day before covering with carpeting or other floor coverings, or loading with heavy objects.

## Protection of the Workplace and the Environment:

Solvent-free and non-flammable, and requires no special protection or precautions in general use. Avoid prolonged contact with skin, or contact with eyes.

## Disposal:

Where possible, collect product residues and re-use. Do not allow into drains, watercourses or landfill. Empty, drip-free plastic or metal containers are recyclable. Containers with liquid residues and liquid waste product are Special Waste. Containers with hardened residues are Construction Waste.

The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the covering manufacturer.

The publication of this Product Data Sheet invalidates all previous Product Data Sheets.



### Pallmann | A Brand of UFLOOR Systems

D | JP Coatings GmbH  
Im Kreuz 6 | D-97076 Würzburg  
Telefon +49 (0)931 27964-0  
Telefax +49 (0)931 27964-50  
E-Mail [info@pallmann.net](mailto:info@pallmann.net)  
Internet [www.pallmann.net](http://www.pallmann.net)

GB | Uzin Ltd.  
4/5 Cholswell Court · Shippon | Abingdon · Oxon OX136HX  
Telephone +44 (0)1235 5341-06  
Telefax +44 (0)1235 5341-07  
E-mail [info@uzin.co.uk](mailto:info@uzin.co.uk)  
Internet [www.uzin.co.uk](http://www.uzin.co.uk)