

9. The oiled parquet surface must not be covered within the first 12 hours following the application of Magic Oil 2K or Magic Oil 2K Colour!
10. To ensure the long life of the floor, we recommend regular care according to the manufacturer's instructions with Magic Oil Care and maintenance cleaning with Pallmann Clean. The exact care intervals should be taken from the care instructions for Magic Oil 2K or Magic Oil 2K Colour.

**Consumption:** 10 – 20 ml/m<sup>2</sup>

#### For wood floors stained with Magic Oil 2K Colour

These cleaning and care instructions apply similarly for treated wood floors. The colour of the stained wood can no longer be achieved after thorough cleaning and subsequent care. We recommend that you have thorough cleaning and re-oiling carried out by a flooring specialist.

**Important instructions:** Contact of the product with pads or textile materials creates the risk of spontaneous ignition! Impregnated clothes, pads etc. should therefore be soaked in water and stored or disposed of in tightly sealed containers. Grinding dusts from oxygen drying systems are also spontaneously inflammable. Danger of fire! On completion of grinding work, the grinding dust should be damped down and disposed of in tightly sealed containers!

To enable you to give your impregnated wood floor the best cleaning and care, an overview of levels of dirt with the corresponding cleaning and care intervals is given below:

Level of soiling	Areas such as	Maintenance cleaning	Thorough cleaning	Maintenance care
Medium	Private living rooms and bedrooms	The frequency of maintenance cleaning depends on the level of soiling and the required hygiene	12 months	approx. every 2 months
Medium-heavy	Stairways, offices, corridors		6 months	approx. every 2 – 4 weeks
Very heavy	Hotels, schools, businesses		2 – 3 months	approx. every 8 – 12 days

### Your parquet fitting business:

A healthy room climate contributes both to well-being of people and to maintaining the value of your wood floor. Wood is a hygroscopic natural material which adapts to the prevailing air humidity by absorbing or giving off moisture to the air. Changes in humidity cause the wood either to swell or contract, which can lead to visible joints in the floor. For this reason, we recommend a room temperature of 18 °C to 20 °C and a relative air humidity of 50 – 60 %. A hygrometer is a useful aid in measuring and controlling the condition of the air in the room. No guarantee is given for the work carried out. In case of doubt, carry out your own tests. The oiled wood floor surface will provide protection with proper application, maintenance of the room air condition and the recommended cleaning and care intervals. These care instructions are valid for all wood floors complying with DIN 18 356 "Parquet flooring work" and DIN 18 367 "Wood plastering work", which are oiled with the products Pallmann Magic Oil 2K and Magic Oil 2K Colour and treated with suitable Pallmann care products.

**Important:** Castors and slides must comply with DIN EN 12 529 (plastic or felt). Metal furniture and objects should be provided with a protective mat.



# Upkeep Instruction for Magic Oil 2K and Magic Oil 2K Colour

Valuable tips for the correct care  
of treated wood floors



**Pallmann** | A Brand of UFLOOR Systems

D | JP Coatings GmbH  
Im Kreuz 6 | D-97076 Würzburg  
Telefon +49 (0)931 27964-0  
Telefax +49 (0)931 27964-50  
E-Mail info@pallmann.net  
Internet www.pallmann.net

GB | Uzin Limited.  
4/5 Cholswell Court Shippon, Abingdon  
Oxon OX13 6HX. United Kingdom.  
Telephone 01235 534106  
Telefax 01235 534107  
E-mail info@uzin.co.uk

**Pallmann**<sup>®</sup>  
gets to the point.

# Maintenance instructions

You have decided on the installation of a natural product, parquet or wood floor which has been ecologically treated with Pallmann Magic Oil 2K.

Oil – waxed wood floors should only be walked on after complete drying – at the earliest after 12 hours. After this time, the treated surface may be allowed to come into contact with water or other non-aggressive fluids. The more carefully the newly oil-waxed wood floor is treated in the first few days, the longer the useful life of the wood floor is assured. The floor should not be exposed to excessive weights, such as furniture before 12 hours. Newly treated wood floors should not be covered with synthetic and/or textile floor coverings or films in the first 12 hours.

## 1. Initial and maintenance care with Pallmann Magic Oil Care

To enable your treated wood floor to withstand day-to-day use, the initial and maintenance care should be carried out using only Pallmann Magic Oil Care.

### Application:

1. The initial care treatment can only be applied to the newly treated wood floor after 12 hours.
2. Allow the product to acclimatise to room temperature before use, and shake well.
3. Clear the floor of dirt, dust and grease using a mop, soft brush or vacuum cleaner.
4. Initial care: Apply Pallmann Magic Oil Care undiluted in an even, thin layer using a mop.
5. Maintenance care: Dilute approx. 500 ml Pallmann Magic Oil Care in 10 litres of water. Apply once, damp (not wet) to the floor using a suitable (fluff-free) mop, working in one direction only, and allow to dry.
6. Clean tools after use with clean water.
7. Maintenance care should be applied depending on the level of traffic.

## 2. Maintenance cleaning with Pallmann Clean

For wood floors treated with Pallmann Magic Oil 2K, maintenance care should be carried out using Pallmann Clean.

### Application:

1. Allow the product to acclimatise to room temperature before use, and shake well.
2. Clear the floor of dirt, dust and grease using a mop, soft brush or vacuum cleaner.
3. The first maintenance cleaning should only be applied to the newly treated wood floor after 12 hours.
4. Maintenance cleaning: Dilute 100 – 200 ml Pallmann Clean in 10 litres of water. Apply once, damp (not wet) to the floor using a suitable (fluff-free) mop, working in one direction only, and allow to dry.
5. Clean tools after use with clean water.
6. Maintenance cleaning should be applied according to the level of dirt on the parquet surface.

## 3. Thorough cleaning with Pallmann Soap Care

**Note: We recommend that you have the thorough cleaning carried out by a flooring specialist.**

### Application:

1. Allow the product to acclimatise to room temperature before use, and shake well.
2. Clear the floor of dirt, dust and grease using a mop, soft brush or vacuum cleaner.
3. Mix the Pallmann Soap Care according to the level of soiling of the floor. For medium levels use approx. 1 – 2 litres to 10 litres of water, and for high levels, use undiluted. The surface to be cleaned should only be wiped damp (not wet).
4. In case of high levels of soiling, remove the dirt from the surface using a brush or rotary floor cleaner (green soft pad).
5. After cleaning, always wipe down the surface with clean water.
6. Clean tools after use with clean water.
7. The number of cleaning processes depends on the level of soiling.
8. The cleaned floor requires re-treating with a coat of Pallmann Magic Oil 2K or Magic Oil 2K Colour, see Point 4.

## 4. Re-oiling with Pallmann Magic Oil 2K or Magic Oil 2K Colour

The frequency of re-oiling with Pallmann Magic Oil 2K or Magic Oil 2K Colour depends on the level of traffic on the floor and the frequency of damp cleaning.

- Re-oiling with Pallmann Magic Oil 2K or Magic Oil 2K Colour should only be carried out after thorough cleaning with Pallmann Soap Care.
- Areas of low traffic and infrequent cleaning – annually.
- Normal living areas – once or twice a year.
- Areas of heavy commercial traffic – monthly to quarterly.

### Application:

1. Allow the product to acclimatise to room temperature before use, and shake well.
2. Mix Magic Oil 2K or Magic Oil 2K Colour with the hardener component and apply evenly to the surface using a suitable tool (e.g. Pallmann lacquer trowel).
3. Remove excess Magic Oil 2K or Magic Oil 2K Colour, 10 – 30 minutes after application using a Pallmann soft pad (green).
4. Immediately after removing the excess from the first coat, apply the second coat of Magic Oil 2K or Magic Oil 2K Colour. Remove any excess at the latest 10 minutes after application of the second coat, again using a Pallmann soft pad (green) and then polish with the polishing pad (white). No excess material should be left on the surface.
5. After approx. 20 minutes, the surface must be polished again with a white pad for a homogenous surface appearance.
6. Due to the different absorption qualities of different types of wood and parquet, a third or fourth application may be necessary as above.
7. Rolling procedure: Apply Magic Oil 2K or Magic Oil 2K Colour 1x thinly and evenly using a Pallmann LSM application roller. Consumption: approx. 70 – 90 ml/m<sup>2</sup>, depending on the type of wood. After approx. 30 minutes, remove any excess material using a lacquer trowel or a rubber squeegee, and polish the complete surface using a Pallmann green soft pad, followed by a Pallmann white polishing pad.
8. Clean tools after use with Pallmann Uni Clean.